



REVISIONS			
DESCRIPTION		DATE	
S	pecification	2024/3/19	
	SPECIFICATION		
	Charging Current: 6 ~16A		
ors			
	Phase Mode: Single Phase		
	Operational Voltage: 230V±10%		
	Rated Operating Frequency: 47 - 63 Hz IP Rating: IP55		
	Insulation Resistance: >10 Ω		
	Insulator Flammability: UL94		
	Withstand Voltage: 2000V		
	Relative Humidity: 0-95% non-condensing		
Maximum Altitude: < 2000M			
	Service Life: 50,000 times		
Working Temperature: -40 °C ~+ 75 °C			
	TYPE 2/IEC 62196-2 female plug		
	(0.75mm²)		
	(0.75mm ²)		
	(2.5mm ²)	-	
	(2.5mm ²)	GREEN&YELLOW	
	(2.5mm ²)	BLUE	
	L1	BROWN	
Wall plug (1-phase, max 16A)			
	(2.5mm ²)		
	PE (2.5mm²)	GREEN&YELLOW	
	(2.5mm²)	BROWN	
•	N (2.5mm ²)	BLUE	
t			
١G	i		
0003 DATE: 2024/3/19			
	SHEET: 1 OF 1	REV.	
		INE V.	
		I	